



DI-1000

Digital Fiber Inspection Microscope

Fiber Optics Connector Inspection Scope

The ergonomically designed DI-1000 connects directly to VeEX test sets through its USB 2.0 port. The DI-1000 features an easy single-finger focusing knob, comprehensive list of tips and digital image sensor and optics with detectable resolution to 0.5 μm .



Dirty or scratched connectors introduce loss, increase ORL and can damage other connectors. End-face contamination is a leading cause of fiber link failures in Telecom, MSOs, data centers, and corporate network environments.

The ergonomically designed VeEX DI-1000 digital fiber inspection scope provides clear images of the connector's end face. Focusing on the contact areas, the DI-1000 grades the connector's health and cleanliness after it is polished or cleaned. The results determine whether the connector can be used or if it needs to be polished or cleaned again.

Platform Highlights

- Precise and stable single-finger focus knob
- One hand operation
- Inspect patch cords and bulkheads
- Compatible with UX400, TX300-Series, FX300, RXT-1200, SunLite OTDR and PCs
- Direct USB 2.0 connection to test set or PC
- Powered by USB
- Robust for field use (no motors or batteries)
- Ergonomic design
- Comprehensive line of tips available
- Quick tip replacement

Auto Focus Detection & Analysis

The DI-1000 is compatible with VeEX test sets offering built-in Pass/Fail analysis with fast and accurate Auto Focus Detection. This technology still relies on the incredible fast response and finesse of human hands, but leaves the focus assessment, image capturing and analysis to the test set. No training is necessary, yet beginners can get it right every time.

- The test set detects when the image has reached optimal focus level, automatically freezes the picture, captures the image and runs the IEC 61300-3-35 analysis
- Much faster focus, acquisition and analysis, compared to slow electro-mechanical auto-focusing scopes
- No need to move the hands or press any buttons (movement and vibration are common causes of focus loss)
- No PC required for image acquisition or Pass/Fail analysis
- Users still remain in control during non-trivial scenarios requiring the irreplaceable human dexterity and ingenuity
- Report generation (html and PDF) directly from the test set
- Compare function for images captured before and after cleaning

Ordering Information

Z06-00-008P DI-1000 Video Fiber Scope, USB 2.0 Version

Recommended Accessories

F99-00-078G Universal 2.5 mm probe tip for PC type male connectors
 F99-00-079G Universal 1.25 mm probe tip for PC type male connectors
 F99-00-080G Probe tip for 1.25 mm male ELIO connectors and termini
 F99-00-081G Universal 2.0 mm probe tip for PC type male termini and LEMO F2
 F99-00-082G Tip for Biconic connectors
 F99-00-095G Tip for SMA 905 male connectors
 F99-00-096G Universal 2.5 mm probe tip for APC type male connectors
 F99-00-097G Universal 1.25 mm probe tip for APC type male connectors
 F99-00-098G Tip for SC and FC PC type female connectors
 F99-00-099G Short Extended tip for FC and SC PC type female connectors
 F99-00-100G Medium Extended tip for FC and SC PC type female connectors
 F99-00-101G Long Extended tip for FC and SC PC type female connectors
 F99-00-102G 60 degree angled tip for FC and SC PC type female connectors
 F99-00-103G Tip for SC and FC APC type female connectors
 F99-00-104G Short Extended tip for SC APC type female connectors
 F99-00-105G 60 degree angled tip for SC APC type female connectors
 F99-00-106G Tip for hardened SC/APC (Optitap®) female connectors
 F99-00-107G Tip for ST PC type female connectors
 F99-00-108G Short Extended tip for ST PC type female connectors
 F99-00-109G Medium Extended tip for ST PC type female connectors
 F99-00-110G Long Extended tip for ST PC type female connectors
 F99-00-111G 60 degree angled tip for ST female connectors
 F99-00-112G Short Extended tip for E2000 PC type female connectors
 F99-00-113G Medium Extended tip for E2000 PC type female connectors
 F99-00-114G Long Extended tip for E2000 PC type female connectors
 F99-00-115G Tip for E2000 APC type female connectors
 F99-00-116G Tip for LC PC type female connectors
 F99-00-117G Short Extended tip for LC PC type female connectors
 F99-00-118G Medium Extended tip for LC PC type female connectors

F99-00-119G Long Extended tip for LC PC type female connectors
 F99-00-120G Tip for LC APC type female connectors
 F99-00-121G Tip for MU PC type female connectors
 F99-00-122G Short Extended tip for MU PC type female connectors
 F99-00-123G Medium Extended tip for MU PC type female connectors
 F99-00-124G Long Extended tip for MU PC type female connectors
 F99-00-125G 60 degree angled tip for MU PC type female connectors
 F99-00-126G Tip for LEMO female connectors (SMPTE F2)
 F99-00-127G Tip for 2.0 mm female termini
 F99-00-128G Tip for 1.6 mm female termini
 F99-00-129G Tip for ELIO 1.25 mm female connectors
 F99-00-130G Tip for LX.5 PC female connectors
 F99-00-131G Tip for LX.5 APC female connectors
 F99-00-132G Extended tip for MTP PC type connectors
 F99-00-133G Front end tip for MTP PC type connectors
 F99-00-134G Extended tip for MTP APC type connectors
 F99-00-135G Front end tip for MTP APC type connectors
 F99-00-136G Extended tip kit for MTP PC and APC connectors

Replacement Items

C02-00-019G Carrying Pouch for Video Fiber Scope with Tips

General

	OTDR Parameters
Field of View	425 µm to 320 µm
Resolution	0.5 µm detectable
Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Focus	Manual adjustment, 2 mm max travel
Dimensions	35 mm diameter x 175 mm length (without tip)
Light Source	Blue LED
Power Supply	USB port of PC



VeEX Inc.
 2827 Lakeview Court
 Fremont, CA 94538 USA
 Tel: +1.510.651.0500
 Fax: +1.510.651.0505
 www.veexinc.com
 customercare@veexinc.com

© 2019 VeEX Inc. All rights reserved.
 VeEX is a registered trademark of VeEX Inc. The information contained in this document is accurate. However, we reserve the right to change any contents at any time without notice. We accept no responsibility for any errors or omissions. In case of discrepancy, the web version takes precedence over any printed literature.
 D05-00-098P B00 2019/7