# Densitron

2U 19" Rack mount ready TFT display with capacitive touch for Broadcast applications. It can be used for signal and picture monitoring, or a control system with the help of multitouch PCT, or a combination of both. Densitron provides a 16.3" high resolution (1920 x 285 display, which allows multiple video picture monitor and audio level displays - side-by-side. **Projected Capacitive Touch** functionality allows the device to be interactive Common signal interfaces, such as: Display port, DVI and VGA are used for video signals; and USB for touch screen.

## 2U 19" Rack Monitoring Control Solutions

#### **Product features**

- Plug and Play display for most operating systems
- Packaged into one 2U 19" rack metal chassis
- High resolution **1920 x 285** in a **2U Active Area** and has an auto detection mode
- True **8-bit colour** depth which provides a **16.7 Million** colour depth
- Pixel per inch 119
- Utilising AHVA (IPS-Like) technology which offer an 85/85/85/85 symmetric viewing angles
- These TFT modules are designed to operate in 24/7 mode with a backlight offering a half-life of 50,000 hours and and an operating temperature range of 0°C to +50°C
- All modules offer Long term availability
- UReady USB family offers 10 finger Projected Capacitive Touch (PCT) as standard
- 500cd/m2 or 800cd/m2 Brightness and Adjustable
- **Single power unit** for controlling both the displays and PCT touch panel





www.densitron.com

	Parameter	Value
	Screen size	16.3″
	Display format	1920 x 285 pixels
	Colour	16.7M, True 8-Bit
	Active area	408.96 x 60.75 mm
L L	Outline dimensions	482.6 x 88 mm
ţi	Viewing angle	85/85/85 degrees
C	Contrast ratio	1000: 1 (Тур.)
Product description	Brightness	500cd/m2
	LED backlight life time	50,000 hourr half-life
	I/O	DVI-D, DP, VGA
	Power	1 x 12V DC input
õ	Power consumption	33W
ā	Operating temperature	$0^{\circ}C \sim +50^{\circ}C$
	Storage temperature	$-10^{\circ}C \sim +60^{\circ}C$
	Mount	19" rack mount
	Case	Durable metal
	Response time	40mS
	Touch	PCT 10 finger, USB
	Weight	2kg



## 2U 19" rack HMI engine

Size	Part number	Description
16.3″	DM-163BD-MPGR06	2U 19" Rack HMI engine with PCT touch

### Related products: 1RU Ready 19"



Size	Part number
3.2″	DMT132YYHLCMU-1D
5.6″	DMT066YYHLCMU-1D

**U**Ready

Contact your local sales office at www.densitron.com

