


FIBER TOOLS

LC-500
Launch Cable

TESTING | TROUBLESHOOTING | ACCURACY



Product Features:

ELIMINATE DEAD ZONES:
Long OTDR pulse widths are suppressed

UNIVERSAL, COMPACT DESIGN:
No need for multiple launch cables for varying network connectors

Typically the technician will use a launch cable on the input and output connectors of the fiber under test. This allows the technician to characterize the insertion and return loss of the input and output connectors of fiber link. Supports SC, LC, FC, and ST connectors (APC + UPC as appropriate). Supplied in a canvas carry pouch with one SC/APC to AC/APC cable.

It is recommended that a one meter patch cord is used at the 930XC OTDR bulkhead. Please refer to the application note "Using a one meter Jumper at the bulkhead".



ORDERING INFORMATION:

CAT. NO.	DESCRIPTION
LC-500	500m Launch Cable, Singlemode



OFL100

1M PATCH CORD

INPUT LAUNCH CABLE



Fiber Under Test

OUTPUT RECEIVE CABLE

Do you like this solution?
Please contact Heynen for distribution in BENELUX.

heynen@heynen.com
BE tel: +32 (0)11-600909
NL tel: +31 (0)485-550909
LUX tel: +352(0)26-910781

TEMPO COMMUNICATIONS

Renewed Vision. Innovation Forward.

Follow us on Social Media
@TempoComms