



FIBER TOOLS

hcy ncn

FI-100

FIBER IDENTIFIER

Fast, Simple Fiber Identification

Product Features:

NON-INTRUSIVE.

Low insertion loss testing prevents alarm conditions.

TONE DETECTION.

Trace injected signals without disconnecting fibers.

VERSATILE.

Supports all common fibers including ribbon cables and can sense light in bend insensitive fibers.





FIBER TOOLS

heynen



Specifications:

Identified Wavelength Range	800-1700nm		
Identified Signal Type	270Hz, 330Hz, 1kHz, 2kHz; (+/-5%)		
Detector Type	1mm InGaAs		
Adapter Types	Ø0.25 (Applicable for Bare Fiber and ribbon cable) Ø0.9 (Applicable for Ø0.9 Cable) Ø2.0 (Applicable for Ø2.0 Cable) Ø3.0 (Applicable for Ø3.0 Cable)		
Signal Indication	Left & Right LED		
Signal Direction Test Range (CW/0.9mm fiber)	-46 to 10dBm (1310nm) -50 to 10dBm (1550nm)		
Signal Power Test Range (CW/0.9mm fiber)	-50 to +10dBm		
Signal Frequency Display	270Hz, 330Hz, 1kHz, 2kHz; (+/-5%)		
Tone Detect Test Range (Average)	Ø0.9, Ø2.0, Ø3.0	-30 to 0dBm (270Hz, 1kHz)	
		-25 to 0dBm (2kHz)	
	Ø0.25	-25 to 0dBm (1kHz, 2kHz)	
		-20 to 0dBm (2kHz)	
Insertion Loss (Typical/ Maximum)	0.3 / 0.8dB at 1310nm 1.5 / 2.5dB at 1550nm		
Battery	AAA Alkaline (2)		
Operating Temperature	-10 to +60°C		
Storage Temperature	-25 to +70°C		
Dimension	196 X 30.5 X 27mm		
Weight	195g		
Certifications	CE, FCC, RoHS, EAC		
Number of Activations	3600		

Ordering Information:

CAT. NO.	DESCRIPTION
FI-100 KIT	Fiber Identifier Kit
FI-100-250/RIB	250µm / Ribbon Adapter
FI-100-900	900µm Adapter
FI-100-2MM	2mm Adapter
FI-100-3MM	3mm Adapter
FI-100-CASE	Soft Carry Case
FI-100-MANUAL	Instruction Manual
FI-100-SUNSHADE	FI-100-SUNSHADE

The **FI-100 KIT** comes complete with all four adapters, instruction manual and a sun shade all packed in a soft carry case.

Do you like this solution?

Please contact Hevnen for distribution in BENELUX.



heynen@heynen.com

NL tel: +31 (0)485-550909

BE tel: +32 (0)11-600909

LUX tel: +352(0)26-910781



TEMPO
COMMUNICATIONS

an ISO 9001 / AS 9100 D (AS9104/1 Issue 2012-01) Company



Follow us on Social Media
@TempoComms